

Undercounter type (100V,220V)

RC : Refrigerating compartment
FC : Freezing compartment

●Refrigerator

W D	650	800	880	1200	1500	1800	2100
450	Non-inverter controlled RC : -7°C to 12°C			Non-inverter controlled RC : -7°C to 12°C Sliding door RC : 0°C to 10°C	Non-inverter controlled RC : -7°C to 12°C	Non-inverter controlled RC : -7°C to 12°C	
600		Non-inverter controlled RC : -5°C to 12°C	220V/240V RC : -6°C to 12°C	220V/240V Inverter controlled RC : -7°C to 12°C 220V/240V RC : -6°C to 12°C 220V/240V non-flap RC : -6°C to 12°C 220V/240V machine unit on the right RC : -6°C to 12°C 220V/240V center non-pillar built-in drainage automatic evaporate unit type RC : -6°C to 12°C Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -7°C to 12°C RC : -5°C to 10°C High humidity freezing temperature -3°C to 6°C humidity : above 85% Power Fresh RC : -5°C to 10°C Sink type RC : -5°C to 10°C Low height RC : -5°C to 10°C drawer table RC : -5°C to 10°C	220V/240V Inverter controlled RC : -7°C to 12°C 220V/240V RC : -6°C to 12°C 220V/240V non-flap RC : -6°C to 12°C 220V/240V machine unit on the right RC : -6°C to 12°C 220V/240V center non-pillar built-in drainage automatic evaporate unit type RC : -6°C to 12°C Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -7°C to 12°C RC : -5°C to 10°C High humidity freezing temperature -3°C to 6°C humidity : above 85% Power Fresh RC : -5°C to 10°C Sink type RC : -5°C to 10°C Sliding door RC : 0°C to 10°C	220V/240V Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -7°C to 12°C RC : -5°C to 10°C High humidity freezing temperature -3°C to 6°C humidity : above 85% Power Fresh RC : -5°C to 10°C	220V/240V RC : -6°C to 12°C 220V/240V center non-pillar RC : -6°C to 12°C Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -7°C to 12°C RC : -5°C to 10°C High humidity freezing temperature -3°C to 6°C humidity : above 85% Power Fresh RC : -5°C to 10°C
750		Non-inverter controlled RC : -5°C to 12°C	220V/240V RC : -6°C to 12°C	220V/240V Inverter controlled RC : -6°C to 12°C 220V/240V RC : -6°C to 12°C 220V/240V non-flap RC : -6°C to 12°C 220V/240V machine unit on the right RC : -6°C to 12°C 220V/240V center non-pillar built-in drainage automatic evaporate unit type RC : -6°C to 12°C Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -5°C to 10°C drawer table RC : -5°C to 10°C Pass through RC : -5°C to 10°C	220V/240V Inverter controlled RC : -6°C to 12°C 220V/240V RC : -6°C to 12°C 220V/240V non-flap RC : -6°C to 12°C 220V/240V machine unit on the right RC : -6°C to 12°C 220V/240V center non-pillar built-in drainage automatic evaporate unit type RC : -6°C to 12°C Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -5°C to 10°C High humidity freezing temperature -3°C to 6°C humidity : above 85% Pass through RC : -5°C to 10°C	220V/240V RC : -6°C to 12°C 220V/240V center non-pillar RC : -6°C to 12°C Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -5°C to 10°C Pass through RC : -5°C to 10°C	220V/240V RC : -6°C to 12°C 220V/240V center non-pillar RC : -6°C to 12°C Inverter controlled RC : -7°C to 12°C Center non-pillar RC : -5°C to 10°C Pass through RC : -5°C to 10°C

●Refrigerator-freezer

W D	650	800	880	1200	1500	1800	2100
450				Non-inverter controlled RC : -7°C to 12°C FC : -25°C to -15°C	Non-inverter controlled RC : -7°C to 12°C FC : -25°C to -15°C		
600				Inverter controlled RC : -7°C to 12°C FC : -25°C to -8°C	Inverter controlled RC : -7°C to 12°C FC : -25°C to -8°C 3 doors RC : -5°C to 10°C FC : -25°C to -15°C	Inverter controlled RC : -7°C to 12°C FC : -25°C to -8°C	Inverter controlled RC : -7°C to 12°C FC : -25°C to -8°C
750				Inverter controlled RC : -7°C to 12°C FC : -25°C to -8°C	Inverter controlled RC : -7°C to 12°C FC : -25°C to -8°C	Inverter controlled RC : -7°C to 12°C FC : -25°C to -8°C	

●Freezer

W D	650	800	880	1200	1500	1800	2100
450	Non-inverter controlled FC : below -20°C			Non-inverter controlled FC : -25°C to -15°C			
600			220V/240V FC : -25°C to -7°C	220V/240V FC : -25°C to -7°C 220V/240V center non-pillar FC : -25°C to -7°C Inverter controlled FC : -25°C to -8°C Center non-pillar FC : -25°C to -8°C	220V/240V FC : -25°C to -7°C 220V/240V center non-pillar FC : -25°C to -7°C Inverter controlled FC : -25°C to -8°C Center non-pillar FC : -25°C to -8°C	220V/240V FC : -25°C to -7°C 220V/240V center non-pillar FC : -25°C to -7°C Inverter controlled FC : -25°C to -8°C Center non-pillar FC : -25°C to -8°C	
750			220V/240V FC : -25°C to -7°C	220V/240V FC : -25°C to -7°C 220V/240V center non-pillar FC : -25°C to -7°C Inverter controlled FC : -25°C to -8°C Center non-pillar FC : -25°C to -8°C	220V/240V FC : -25°C to -7°C 220V/240V center non-pillar FC : -25°C to -7°C Inverter controlled FC : -25°C to -8°C	220V/240V FC : -25°C to -7°C 220V/240V center non-pillar FC : -25°C to -7°C	